

## CaprizPlus Specification

CaprizPlus	24kW	28kW
<b>Size</b>		
Casing dimensions (h w d) (mm)	740/425/330	740/425/330
Weight (lift)	36.7kg	36.9kg
<b>Performance</b>		
CH output (kW) Min/Max	7.8/17.6	9.2/23.2
DHW output (kW) Min/Max	8/24	9.5/28
DHW flow rate storage/combi (l/min. 35°C rise)	9.4	11.2
SEDBUK rating 2009	90	88.5
Nox class 5 (natural gas)	Yes	Yes
LPG Compatible	Yes	Yes
<b>Construction</b>		
Main heat exchanger type	Coiled tube	Coiled tube
Heat exchanger material	Stainless steel	Stainless steel
Burner type	Pre-mixed	Pre-mixed
Fully modulating	Yes	Yes
DHW plate heat exchanger	Yes	Yes
Integrated hydrobloc	Yes	Yes
<b>Installation</b>		
Suitable for sealed systems	Yes	Yes
Suitable for open-vent systems	No	No
Filling loop	No	No
Inbuilt automatic bypass	Yes	Yes
Inbuilt adjustable system bypass	No	No
Inbuilt condensate trap/siphon	Trap	Trap
Inbuilt boiler frost protection	2 stage	2 stage
Zero compartment ventilation	Yes	Yes
<b>Clearances</b>		
Top (mm) (from top of boiler)	200	200
Side (mm)	5	5
Bottom (mm)	300	300
Front (mm) <sup>2</sup>	600	600
<b>User Interface</b>		
User adjustable CH temp control	Yes	Yes
User adjustable DHW temp control	Yes	Yes
Eco setting on DHW	No	No
Pre-fitted analogue timer	Yes	Yes
<b>Pipes</b>		
Pre-fixing jig	No	No
Optional spacing frame	No	No
Water connections	2x22/2x15mm	2x22/2x15mm
<b>Flues</b>		
Max horizontal Ø60/100	8m	8m
Max vertical Ø60/100	8m	8m
Optional plume management kit Ø60/100	Yes	Yes

## CaprizPlus Specification

